

What is claimed is:

1. A plasma display panel comprising;
a front plate and a back plate parallel to and facing each other having a space therebetween for a discharge gas,
plural pairs of display electrodes for surface discharge on the front plate parallel to each other, with each display electrode pair comprising a sustain electrode and a bus electrode,
a dielectric layer covering the display electrodes, and a protective film overlying the dielectric layer,
address electrodes on the back plate at right angles to the display electrode pairs, and a dielectric layer covering the address electrodes, and
linear ribs located between the address electrodes, with phosphor layers located between the adjacent linear ribs so that they each extend intermittently in the lengthwise direction of the ribs for each pixel.

2. The plasma display panel as claimed in claim 1, further comprising linear shield layers on the front plate parallel to each other, wherein each shield layer is located between an adjacent display electrode pair to be parallel to the display electrode pairs.

3. A plasma display panel comprising;
a front plate and a back plate parallel to and facing each other having a space therebetween for a discharge gas,

plural pairs of display electrodes for surface discharge on the front plate parallel to each other, with each display electrode comprising a sustain electrode and a bus electrode,

a dielectric layer covering the display electrodes, and a protective film overlying the dielectric layer,

address electrodes on the back plate at right angles to the display electrode pairs, and a light-absorbing layer covering the address electrodes, and

linear ribs located between the address electrodes, with phosphor layers located between the adjacent linear ribs so that they each extend intermittently in the lengthwise direction of the ribs for each pixel.

4. The plasma display panel as claimed in claim 3, wherein the light-absorbing layer contains a dark pigment and a dielectric substance.

6. The plasma display panel as claimed in claim 5, further comprising linear shield layers on the front plate parallel to each other, wherein each shield layer is between the adjacent display electrode pairs and parallel to the display electrode pairs.

Sub
D1

7. A back plate for plasma display panels, which comprises;

a plurality of linear address electrodes on a glass substrate, a dark dielectric layer covering the address electrodes, and linear ribs between the address electrodes, and

phosphor layers located between the adjacent linear ribs so that a red-emitting phosphor layer, a blue-emitting phosphor layer and a green-emitting phosphor layer are adjacent each other with a rib therebetween and these three different phosphor layers each extend intermittently in the lengthwise direction of the ribs.

0023190-040699

Sub
A1

8. The back plate for plasma display panels as claimed in claim 7, wherein the dark dielectric layer contains a dark pigment and a dielectric substance.

Sub
D1

9. A plasma display panel comprising;
a front plate and a back plate parallel to and facing each other having a space therebetween for a discharge gas,
plural pairs of display electrodes for surface discharge on the front plate parallel to each other, with each display electrode pair comprising a sustain electrode and a bus electrode,
a dielectric layer covering the display electrodes, and a protective film overlying the dielectric layer,
address electrodes on the back plate at right angles to the display electrode pairs, and a dielectric layer covering the address electrodes, and
linear ribs located between the address electrodes, with a phosphor layer located in each of a plurality of adjacent cell spaces formed by a plurality of adjacent linear ribs, said phosphor layers being intermittently interrupted so that they do not exist in the regions on the back plate which correspond to the region between the adjacent display electrode pairs.

10. The plasma display panel as claimed in claim 9, further comprising shield layers in the regions between the adjacent and parallel to the display electrode pairs on the front plate.

Sub
D1

11. The plasma display panel as claimed in claim 9, further comprising a dark layer on the entire surface of the back plate below the linear ribs and below the phosphor layers.

12. A method for forming a phosphor screen for a plasma display panel, comprising the steps:

(1) applying a photosensitive phosphor paste between linear ribs located between address electrodes on a back plate,

(2) drying the phosphor paste on the back plate,

(3) exposing the dried photosensitive phosphor paste through a photomask having a pattern masking regions to separate subpixels to undergo surface discharge,

(4) developing the exposed photosensitive phosphor paste to produce a pattern of remaining phosphor layers which comprise predetermined individual subpixels,

repeating steps (1)-(4) steps for three different color phosphors to form a phosphor screen, and

(5) baking the resulting phosphor screen.